

| Model | COM | Ethernet | Monitoring | Alarm | Data Record | Validity | WIFI / 4G | Pass-through | Script |
|------------|--------|----------|------------|-------|-------------|-----------------------|-----------|--------------|--------|
| V-BOX E-00 | 2 in 1 | 1 | 200 | 50 | 20 | 60 days /100 millions | N/A | Serial | N/A |
| V-BOX E-4G | 2 in 1 | 1 | 250 | 100 | 50 | 90 days /100 millions | 4G | Serial | YES |

SPECIFICATIONS

| Items | V-BOX E-00 | V-BOX E-4G |
|-----------------------|------------|---|
| OS | | Linux |
| CPU | | RAM 9 |
| Flash | | 128MB |
| RAM | | DDRIII 64MB |
| SD Card | | N/A |
| USB | | OTG USB / Device USB |
| Serial Port | | COM1: RS232, RS422 / RS485 (2 in 1) |
| Ethernet Port | | 1 Ethernet port |
| WIFI | | N/A |
| Power Supply | | 24VDC (12~28VDC) |
| Power Consumption | | <10W |
| Enclosure | | Metal shell |
| Dimension(W*H*D) | | 101.0mm*73.2mm*26.8mm |
| Mounting Size | | 110.0mm*15.6mm |
| Weight (KG) | | 0.26 |
| Vibration Resistance | | 10~25Hz (X, Y, Z direction 2G/30 minutes) |
| Storage Temperature | | -20°C~70°C |
| Working Temperature | | -10°C~60°C |
| Relative Humidity | | 10~85% RH (Non-condensing) |
| CE Certification | | CE marked |
| FCC Certification | | FCC Class A |
| Http Interface | | Yes |
| Remote Update | | Yes |
| Configuration Backup | | Yes |
| Off-line Transmission | | Yes |
| GPS | N/A | LBS |

